

## LED Sensor Panel Series 3

### SPECIFICATIONS

VOLTAGE	220-240AC
POWER FACTOR	>0.90
CRI	>80
IP RATING	IP20
BEAM ANGLE	110°
INSTALL ACCESSORIES	Surface Mount Kit Recessed Frame Suspension Kit

#### Occupancy and Daylight built in Microwave Sensor:

MOUNTING HEIGHT	3.5m
DETECTION RANGE	8m Diameter
DAYLIGHT THRESHOLD	450 Lux
MOTION HOLD	20mins
STANDBY	30% dim
ACCESSORIES	Remote Control



### ILUMINOUS MODELS

MODEL	POWER	LCP	LUMEN	DIMENSIONS	CCT
PPAN14W3X123KES	14w	13.45w	2300	294*1194*30mm	3000K
PPAN14W3X124KES					4000K
PPAN14W3X125KES					5000K
PPAN14W3X126KES					6000K
PPAN20W3X123KES	20w	19.21w	3300	294*1194*30mm	3000K
PPAN20W3X124KES					4000K
PPAN20W3X125KES					5000K
PPAN20W3X126KES					6000K
PPAN14W6X63KES	14w	13.49w	2300	594*594*30mm	3000K
PPAN14W6X64KES					4000K
PPAN14W6X65KES					5000K
PPAN14W6X66KES					6000K
PPAN20W6X63KES	20w	19.28w	3300	594*594*30mm	3000K
PPAN20W6X64KES					4000K
PPAN20W6X65KES					5000K
PPAN20W6X66KES					6000K

### GET IN TOUCH

 [info@primsal.com](mailto:info@primsal.com)

 [primsal.com](http://primsal.com)